

FiberPRO™

FOAM CONTROL



Concentrate

Liquid Defoamer

This highly concentrated product quickly penetrates and knocks down foam to eliminate problems associated with recovery tank foaming.

USES

- Recommended for use in recovery tanks of extraction machines or automatic scrubbers where foaming might be a problem.
- Carpet extraction recovery tanks.
- Automatic scrubber recovery tanks.
- Sewage systems.
- Water fountains.
- Whirlpools.

BENEFITS

- **Fast Acting** - Breaks foam on contact.
- **Saves Time** - Eliminate downtime and wasted effort in dumping recovery tanks.
- **Versatile** - Has many uses, can be used anywhere foaming is a problem.

PROPERTIES

Color Milky white
Dilution Use as necessary, until foam subsides
Flash point None
Fragrance Characteristic
pH 7.0 - 8.0



DIRECTIONS FOR USE

Read the entire label before using this product.

Shake or mix container well before using. **EXTRACTORS OR AUTOMATIC SCRUBBERS:** Initially place 1 oz. of defoamer per gallon capacity of the pick up tank (8 mL/L) 1:128. If carpet is full of shampoo from previous cleanings, more defoamer may be needed. **SEWAGE SYSTEMS OR WATER PLANTS:** Add defoamer, wait a few minutes for it to disperse, continue until suds subside.

SAFETY

Keep out of reach of children. For institutional and commercial use.

CAUTION: Contains emulsifiers. May cause eye irritation. Avoid contact with eyes.

FIRST AID: If splashed on skin, wash with soap and water. If splashed in eyes, flush with large quantities of water. If swallowed, dilute with two glasses of water. Call a physician.

AVAILABLE IN

Case/ 4 - 1 Gallon (3.78 L): #40304

Drum/55 Gallon (208 L): #40355

Authorized Betco Distributor:

Better Resources. Better Results.
BETCO®

1001 Brown Avenue • P.O. Box 3127 • Toledo, Ohio 43607-0127
©All Rights Reserved 12/01 • Reorder #40392 • email@betco.com • www.betco.com