


HYBRID®



Optically Energized • Extended Wear Floor Finish

A revolutionary new polymer system formulated with XBF technology that provides the longest lasting finish ever. This self sealing, extended wear formula retains film integrity and outstanding gloss even after repeated detergent mopping and burnishing. This finish effectively reduces maintenance and prolongs the time between strippings. Specifically formulated for medium maintenance programs, this product will retain its gloss between burnishings. In high speed programs it greatly reduces the need to frequently use a restorer.

USES

- Linoleum
- Resilient tile
- Terrazzo



BENEFITS

- Extended wear formula provides the longest lasting shine possible.
- Self sealing formulation.
- Applies easily with all types of applicators.
- Will not streak, puddle or fisheye.

PROPERTIES

| | |
|---------------------------------------|--------------------------------|
| Color (dried film) | Crystal clear |
| Color (liquid) | White |
| Coverage | 2000 - 3000 square feet/gallon |
| Drying time | 20 - 30 minutes |
| Fragrance | Mild |
| Freeze/thaw stability | 3 cycles |
| Gloss (ASTM D 1455-87) One Coat | 77 |
| Two Coats | 91 |
| Heel mark resistance | Excellent |
| Leveling | Outstanding |
| Nonvolatile solids | 25% |
| pH | 8.2 - 8.9 |
| Powdering resistance | Excellent |
| Shelf life | 1 year |
| Total solids | 29.3% |

* Utilizes Betco's XBF technology for added brightness and extended durability.

DIRECTIONS FOR USE

Read the entire label before using this product.

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. 4 - 5 coats of finish are recommended.

Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a floor sealer will enhance gloss and long term performance.

ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. **INTERIM MAINTENANCE:** Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.**

SAFETY

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Contains emulsifiers. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician.

AVAILABLE IN

Case/4 - 1 Gallon (3.78 L): #66004
Pail/4 - 1.125 Gallon Bags (4.25 L): #66045
Pail/5 Gallon (18.9 L): #66005
Drum/55 Gallon (208 L): #66055

Authorized Betco Distributor:



CLASSIFIED BY:
Underwriters Laboratories Inc.®
AS TO SLIP RESISTANCE ONLY.

Better Resources. Better Results.
BETCO®